

**SafeSpace**  
PLATFORM


**BuildMan**<sup>®</sup>  
Grade

# SAFESPACE<sup>™</sup> PLATFORM FIBERGLASS STEP LADDER

**HEAVY-DUTY**

- 360° Safespace<sup>™</sup> working area for optimal comfort
- Spacious platform, equivalent to being on the ground (dimension 16 ½" x 16 ½")
- Hip-level guardrail provides additional support
- Anti-slip steps and podium made of aluminum
- Protected internal spreaders for transport and daily use

**METALTECH**<sup>®</sup>



**BUILT TOUGH FOR  
SAFETY**

# BuildMan<sup>®</sup> Grade

## SAFESPACE<sup>™</sup> PLATFORM FIBERGLASS STEP LADDER

ANSI  
TYPE  
IA

The platform makes this unit the number one choice for constant work at heights, increasing user comfort. Reducing fatigue, it gives the user the sensation and stability of working on the ground. If needed, you can lean on the upper bar at hip level for maximum comfort and support. Multiple step ladder sizes are available to work at heights confidently over an extended period of time.

**SafeSpace<sup>™</sup>**  
PLATFORM



SPACIOUS 16 1/2" X 16 1/2"  
ALUMINUM PLATFORM



HIP-LEVEL GUARDRAIL WITH  
VERSATILE TOOL SLOTS



NON-CONDUCTIVE  
FIBERGLASS

PROTECTED INTERNAL  
SPREADERS

HEAVY DUTY FEET  
SLIP RESISTANT



	8' REACH	9' REACH	10' REACH
OPEN DIMENSIONS (W X D X H)	25.75 X 30.75 X 57.75 IN. (65.4 X 78.1 X 146.7 CM)	27.25 X 37.25 X 69 IN. (69.2 X 94.6 X 175.3 CM)	29 X 43.25 X 80.5 IN. (73.7 X 109.9 X 204.5 CM)
CLOSED DIMENSIONS (W X D X H)	25.75 X 8.75 X 62.75 IN. (65.4 X 22.2 X 159.4 CM)	27.25 X 8.75 X 75 IN. (69.2 X 22.2 X 190.5 CM)	29 X 8.75 X 87 IN. (73.7 X 22.2 X 221 CM)
NOMINAL SIZE	2 FT (0.6 M)	3 FT (0.9 M)	4 FT (1.2 M)
MAXIMUM REACH*	8 FT 8 IN. (2.6 M)	9 FT 8 IN. (3 M)	10 FT 7 IN. (3.2 M)
HIGHEST STANDING LEVEL	1 FT 11 IN. (0.6 M)	2 FT 11 IN. (0.9 M)	3 FT 10 IN. (1.2 M)
PLATFORM DIMENSIONS	16.5 X 16.5 IN. (41.9 X 41.9 CM)	16.5 X 16.5 IN. (41.9 X 41.9 CM)	16.5 X 16.5 IN. (41.9 X 41.9 CM)
STEP DEPTH	3 IN. (7.6 CM)	3 IN. (7.6 CM)	3 IN. (7.6 CM)
LOAD CAPACITY**	300 LB (136 KG)	300 LB (136 KG)	300 LB (136 KG)
WEIGHT	23.8 LB (10.8 KG)	28.3 LB (12.8 KG)	32.9 LB (14.9 KG)
STANDARDS	ANSI TYPE IA, CSA GRADE 1A	ANSI TYPE IA, CSA GRADE 1A	ANSI TYPE IA, CSA GRADE 1A
MATERIAL	FIBERGLASS	FIBERGLASS	FIBERGLASS
MODEL	E-PSFB2T1A	E-PSFB3T1A	E-PSFB4T1A
UPC	778300007974	778300007981	778300007998

\*Max. reach: Calculated with a 5'-9" (1.75 m) person with a vertical 12" (30 cm) reach

\*\*Load capacity: Includes weight of user plus materials

# METALTECH<sup>®</sup>

[www.d1safety.com](http://www.d1safety.com)

[info@d1safety.com](mailto:info@d1safety.com)

Metaltech is a registered trademark of Metaltech-Omega inc. | [www.metaltech-omega.com](http://www.metaltech-omega.com) | NOTE: Pictures and descriptions in this brochure may differ from actual product. S-PSFB-NA-EN01